



SAFETY DATA SHEET

Label Remover Spray

SDS according to Regulation (EC) No. 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), Annex II-EU

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Date issued 27.02.2015

Revision date 27.10.2015

1.1. Product identifier

Product name BIZERBA Label Remover Spray 200ml

Specification No. 95948900000

Article no. L10099000019

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product group Aerosols

Use of the substance/preparation Label remover

Relevant identified uses SU21 Consumer uses: Private households (= general public = consumers)

SU22 Professional uses: publicly accessible (administration, education, entertainment, services, craftsmen)

PC35 Washing and cleaning products (including solvent based products)

PROC11 Non-industrial spraying

ERC8A Wide dispersive indoor use of processing aids in open systems

ERC8D Wide dispersive outdoor use of processing aids in open systems

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Distributor

Company name Kleinmann GmbH

Postal address Am Trieb 13

Postcode D-72820

City Sonnenbuehl

Country Germany

Tel +49(0)7128/9292-15

Fax +49(0)7128/9292-415

E-mail chemie@kleinmann.net

Website <http://www.kleinmann.net>

Enterprise no. DE 146 487

1.4. Emergency telephone number

Emergency telephone 8-12, Mo.-Fr.:+49(0)7128/9292-15

SECTION 2: Hazards identification

2.1. Classification of substance or mixture

Classification according to Aerosol 1;H222;

Regulation (EC) No 1272/2008 H229;

[CLP/GHS] Skin Sens. 1;H317;

STOT SE3;H336;

Aquatic Chronic 2;H411;

Substance / mixture hazardous properties

EUH 066;
Pressurized container: Do not pierce or burn, even after use.
Do not expose to temperatures exceeding 50 °C/122 °F.

2.2. Label elements

Hazard Pictograms (CLP)



Composition on the label

Hydrocarbons, C7-C9, n-Alkan, Isoalkan, Cyclics, (R)-p-Mentha-1,8-diene

Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
EUH 066 Repeated exposure may cause skin dryness or cracking.
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear eye protection/protective gloves.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122°F.

Precautionary statements

2.3. Other hazards

Description of hazard

Skin contact: May be slightly irritating on protracted or repeated exposure.
Skin contact may cause redness, smarting and itching.
Vapour or splashes to the eyes may cause redness, smarting and discomfort.
Inhalation of high contents may cause headache, nausea and dizziness.
Inhalation of aerosol/spray mist may cause slight irritation in the upper respiratory tract with symptoms like coughing and sneezing.
Aerosol containers can explode when heated, due to excessive pressure build-up.
Extremely flammable.

Environmental effects

This product does not contain any PBT or vPvB substances.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substance	Identification	Classification	Contents
Hydrocarbons, C7-C9, n-Alkan, Isoalkan, Cyclics	EC no.: 920-750-0 Registration number: 01-2119473851-33-xxxx	Xn,F,N; R11,R51/53,R65, R67 Flam. Liq. 2;H225; Asp. tox 1;H304; Aquatic Chronic 2;H411; STOT SE3;H336; EUH 066;	50 - 100 %
Butane	CAS no.: 106-97-8	Flam. gas 1; H220	10 - 25 %

	EC no.: 203-448-7 Index no.: 601-004-00-0 Synonyms: Butane	Press. Gas Note : C	
Propane	CAS no.: 74-98-6 EC no.: 200-827-9 Index no.: 601-003-00-5	Flam gas 1; H220 Press. Gas	2,5 - 10 %
Isobutane	CAS no.: 75-28-5 EC no.: 200-857-2 Index no.: 601-004-00-0	Flam gas 1; H220 Press. Gas	1 - 2,5 %
(R)-p-Mentha-1,8-diene	CAS no.: 5989-27-5 EC no.: 227-813-5 Index no.: 601-029-00-7 Registration number: 01-2119529223-47-xxxx	R10 R43 Xi; R38 N; R50, R53 Flam. Liq. 3;H226; Flam. Liq. 3;H226; Skin Irrit. 2;H315; Skin Irrit. 2;H315; Skin Sens. 1;H317; Skin Sens. 1;H317; Aquatic Acute 1;H400; Aquatic Acute 1;H400; Aquatic Chronic 1;H410; Aquatic Chronic 1;H410;	1 - 2,5 %
		Note : C	
Hydrocarbons		Xn; R65 Asp. tox 1;H304;	1 - 2,5 %

Substance comments The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.
>30%: alifatic hydrocarbons , perfume

SECTION 4: First aid measures

4.1. Description of first aid measures

General	Remove victim immediately from source of exposure.
Inhalation	Move the exposed person to fresh air at once. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Immediately flush with plenty of water or eyewash solution for up to 10 minutes.
Ingestion	Rinse mouth with water. Immediately give a couple of glasses of water or milk, provided the victim is fully conscious. Do not induce vomiting. Consult a physician for specific advice.

4.2. Most important symptoms and effects, both acute and delayed

Acute symptoms and effects As described in section 2.2, 2.3 and 11.

4.3. Indication of any immediate medical attention and special treatment needed

Other Information If unconscious: Call an ambulance/physician immediately. Show this Safety Data Sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water

Improper extinguishing media fog.
Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire and explosion hazards Aerosol containers can explode when heated, due to excessive pressure build-up. Gases that are dangerous to health may be formed in a fire: carbon monoxide (CO) , carbon dioxide (CO₂) .

5.3. Advice for firefighters

Personal protective equipment Wear personal protective equipment, see section 8. Avoid breathing of combustion gases. Wear self contained breathing apparatus during fire fighting.
Fire fighting procedures Containers close to fire should be removed immediately or cooled with water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal protection measures For personal protection, see section 8. Do not smoke, use open fire or other sources of ignition.

6.2. Environmental precautions

Environmental precautionary measures Contain spillages with sand, earth or any suitable adsorbent material. Provide ventilation and confine spill. Do not allow runoff to sewer. Do not let washing down water contaminate ponds or waterways. Contact local authorities in case of spillage to drain/aquatic environment.

6.3. Methods and material for containment and cleaning up

Cleaning method Clean contaminated area with oil-removing material. For waste disposal, see section 13.

6.4. Reference to other sections

Other instructions See section 8 and section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling Avoid contact with skin and eyes. Avoid inhalation of vapours and spray mists. Keep away from heat, sparks and open flame. Provide good ventilation. Mechanical ventilation or local exhaust ventilation may be required. Risk of vapour concentration on the floor and in low-lying areas. Take precautionary measures against static discharges. Do not eat, drink or smoke when using the product. Wash hands before breaks and before smoking, eating or drinking.

7.2. Conditions for safe storage, including any incompatibilities

Storage Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Always store proper, out of the reach of children and not together with food, feed, medicine and the like. Store at moderate temperatures in dry, well ventilated area.

7.3. Specific end use(s)

Specific use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure limit values

Substance	Identification	Value	TWA Year
Hydrocarbons, C7-C9, n-Alkan, Isoalkan, Cyclics	EC no.: 920-750-0 Registration number: 01-2119473851-33-xxxx		

Butane	CAS no.: 106-97-8 EC no.: 203-448-7 Index no.: 601-004-00-0 Synonyms: Butane	8-hour TWA: 600 ppm 8-hour TWA: 1450 mg/m ³ 15 min.: 750 ppm 15 min.: 1810 mg/m ³	2011
Propane	CAS no.: 74-98-6 EC no.: 200-827-9 Index no.: 601-003-00-5		
Isobutane	CAS no.: 75-28-5 EC no.: 200-857-2 Index no.: 601-004-00-0		
(R)-p-Mentha-1,8-diene	CAS no.: 5989-27-5 EC no.: 227-813-5 Index no.: 601-029-00-7 Registration number: 01-2119529223-47-xxxx	8-hour TWA: 75 ppm	

8.2. Exposure controls

Limitation of exposure on workplace

Working place and methods must be arranged in order to avoid any direct contact with the product. All handling to take place in well-ventilated area.

Safety signs



Respiratory protection

Respiratory protection

If ventilation is insufficient, use a respirator with type A (EN 141) gas filter and P2 particle filter (EN 143/EN 149).

Hand protection

Hand protection

Protective gloves are recommended. Nitrile gloves are recommended. Breakthrough time: >2 hours.

Eye / face protection

Eye protection

Wear approved, tight fitting safety glasses where splashing is probable. Use approved safety goggles or face shield. (EN 166).

Skin protection

Skin protection (except hands)

Wear appropriate clothing to prevent reasonably probable skin contact.

Thermal hazards

Thermal hazards

See section 5.

Appropriate environmental exposure control

Environmental exposure controls

See section 6.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Aerosol.
Colour	Colourless.
Odour	Lemon.
Comments, pH (as supplied)	No data recorded.
Comments, pH (aqueous solution)	Not relevant.
Comments, Melting point / melting range	Not relevant.
Boiling point / boiling range	Value: 65 °C
Flash point	Value: < 0 °C

Comments, Evaporation rate	No data recorded.
Comments, Explosion limit	No data recorded.
Vapour pressure	Value: < 1,10 bar Test temperature: 50 °C
Comments, Vapour density	No data recorded.
Specific gravity	Value: < 1 g/ml
Comments, Bulk density	Not relevant.
Solubility in water	insoluble
Comments, Partition coefficient: n-octanol / water	No data recorded.
Comments, Spontaneous combustability	No data recorded.
Comments, Decomposition temperature	No data recorded.
Comments, Viscosity	Not relevant.
Explosive properties	Not explosive.
Oxidising properties	Does not meet the criteria for oxidising.

9.2. Other information

Other physical and chemical properties

Comments	No information required.
----------	--------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Flammable. Risk of ignition.
------------	------------------------------

10.2. Chemical stability

Stability	Stable under normal temperature conditions and recommended use.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	See section 10.4 and section 10.5.
------------------------------------	------------------------------------

10.4. Conditions to avoid

Conditions to avoid	Avoid exposing aerosol containers to high temperatures or direct sunlight. Avoid heat, flames and other sources of ignition.
---------------------	---

10.5. Incompatible materials

Materials to avoid	No data recorded.
--------------------	-------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Gases that are dangerous to health may be formed in a fire: carbon dioxide (CO ₂) , carbon monoxide (CO) .
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological Information:

Other toxicological data	Toxicological tests on the product has not been performed.
--------------------------	--

Potential acute effects

Inhalation	Vapours may cause drowsiness and dizziness. Inhalation of high vapour concentrations may cause symptoms such as mild irritation, headache, dizziness, fatigue, nausea and in serious cases unconsciousness. Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication.
Skin contact	Skin contact may cause redness, smarting and itching. Prolonged or repeated exposure may degrease the skin with symptoms like redness, smarting, itching, cracking of skin and possible eczema.

Eye contact	May cause temporary eye irritation.
Ingestion	May cause nausea, headache, dizziness and intoxication. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Symptoms of Exposure

Symptoms of overexposure	High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.
--------------------------	--

SECTION 12: Ecological information

12.1. Toxicity

Aquatic, comments	No data available for the product.
-------------------	------------------------------------

12.2. Persistence and degradability

Persistence and degradability	The product is readily biodegradable.
-------------------------------	---------------------------------------

12.3. Bioaccumulative potential

Bioaccumulative potential	The product does not contain any substances expected to be bioaccumulating.
---------------------------	---

12.4. Mobility in soil

Mobility	No data recorded.
----------	-------------------

12.5. Results of PBT and vPvB assessment

PBT assessment results	This product does not contain any PBT or vPvB substances.
------------------------	---

12.6. Other adverse effects

Environmental details, summation	Product is toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
----------------------------------	--

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Specify the appropriate methods of disposal	Do not dispose of residues and waste down the drains. Dispose of waste and residues in accordance with local authority requirements.
Product classified as hazardous waste	Yes
Packaging classified as hazardous waste	Yes
EWC waste code	EWC: 150110 packaging containing residues of or contaminated by dangerous substances
Other Information	Waste code applies to product remnants in pure form. When handling waste, consideration should be made to the safety precautions applying to handling of the product.

SECTION 14: Transport information

14.1. UN number

ADR	1950
RID	1950
IMDG	1950
ICAO/IATA	1950

14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
IMDG	AEROSOLS
ICAO/IATA	AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR	2.1
RID	2.1

IMDG 2.1
ICAO/IATA 2.1

14.4. Packing group

Comments Not relevant.

14.5. Environmental hazards IMDG Marine pollutant: yes

14.6. Special precautions for user

EmS F-D, S-U

Special safety precautions for user None.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Additional information.

Additional information. Not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-directive Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.

Legislation and regulations The Aerosol Dispensers Regulations 2009 (SI 2824), with amendments. EH40/2005, Workplace exposure limits 2005, with amendments. The List of Wastes (England) (Amendment) Regulations 2005. (SI 2005 No. 895). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

15.2. Chemical safety assessment

Chemical safety assessment performed No

SECTION 16: Other information

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS] Aerosol 1; H222; ; EUH 066; Skin Sens. 1; H317; STOT SE3; H336; Aquatic Chronic 2; H411; ; H229;

List of relevant R-phrases (under headings 2 and 3). R67 Vapours may cause drowsiness and dizziness. R38 Irritating to skin. R43 May cause sensitization by skin contact. R50 Very toxic to aquatic organisms. R11 Highly flammable. R65 Harmful: may cause lung damage if swallowed. R10 Flammable. R53 May cause long-term adverse effects in the aquatic environment. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

List of relevant H-phrases (Section 2 and 3). H304 May be fatal if swallowed and enters airways. H222 Extremely flammable aerosol. H226 Flammable liquid and vapour.

	H336 May cause drowsiness or dizziness.
	H400 Very toxic to aquatic life.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H220 Extremely flammable gas.
	EUH 066 Repeated exposure may cause skin dryness or cracking.
	H225 Highly flammable liquid and vapour.
	H410 Very toxic to aquatic life with long lasting effects.
	H229 Pressurised container: May burst if heated.
	H411 Toxic to aquatic life with long lasting effects.
Training advice	No particular training or education is required but the user must be familiar with this SDS. Users must be carefully instructed in the proper work procedure, the dangerous properties of the product and the necessary safety instructions.
Information which has been added, deleted or revised	Change to Sections: 1, 9, 14, 16
Version	3
Responsible for safety data sheet	Kleinmann GmbH
Prepared by	ANI